

HD SNG12



HD SNG12

General information

Maximum cameras

5

Maximum SloMo positions

1

Dimensions

7 m, 2 m, 3 m

Operational area


8,5 m x 3 m

Power requirement

32A CEE (3P+N+E)

Weight

5.5 t



SNG Van

Production area with slow motion, audio and vision control area

Up to 5 workspaces

Grass Valley LDK3000 series cameras

BlackMagic Design ATEM 2ME Broadcast Studio (4ME capability)

TSL TallyMan control system

Lawo mc² 36 audio console, with 16 faders

Riedel Tango intercom system,

Mediornet fiber transport system

NEC and BON monitors


Built in generator and

UPS system

HD SNG12

PRODUCTION AREA

- BlackMagic Design ATEM 2ME Broadcast Studio
 - 1ME 10 button control panel
 - 20 inputs, 11 outputs
 - 2 M/E, 2 keyers per M/E
 - 1ch DME, SuperSource function (4 resizer and foreground key)
 - 4 channel internal ClipStore (with alpha channel)
- 2x LCD 32" NEC Monitor
- BlackMagic multiviewer




VISION CONTROL AREA

- 1x BON 21" Monitor
- 2x Marshall triple monitors
- Nevion SL-3GHD3232 router
- Riedel MicroN video, audio processor
- PHABRIX RK2000 measurement device

CAMERAS

- Up to 5 cameras
 - Grass Valley LDK 3000
 - Vislink INCAM-G Wireless camera with LDX80 camera head



HD SNG12

AUDIO SYSTEM

- Lawo mc² 36 audio console 16 faders
- Up to 96 full Broadcast DSP channels
- 1 external MADI interface
- 1x remote Stagebox, 32 inputs - 32 outputs, 8 AES pairs,
1 MADI connection
- Genelec 8020 Loudspeaker System

INTERCOM

- Riedel Tango
- 2x external intercom keypanels
- 1 external MADI interface
- 1x remote Stagebox, 32 inputs - 32 outputs, 8 AES pairs,
1 MADI connection

RECORDING

- 1x EVS XT[3] 8 CH
- 1x Sony XDCAM recorder



UPLINK

- 1x PROSAT SOLUTIONS D120M Antenna
- 2x XICOM XTD 400K HPA
- 2x ADTEC EN-200 Encoder, modulators

